









Product Features:

4815W3B Part Number:



- 1) 3528 SMD Everlight as the light source- A super Luminous Flux
- 2) Large Veiwing angle with even light shadow ≥ 120°
- 3) Lower Light decay and longer life span up to 50,000 hrs
- 4) Lower Cost / High performance & color uniformity
- 5) Low operating Voltage, energy saving, and environmentally friendly
- 6) Suitable for Backlighting channel letters and Light boxes.
- 7) Suitable for Accent and Edge Lighting
- 8) Waterproof: > IP65

619~635

9) Easy installation and maintenance free

512~528

No' of LEDs per sq Meter

Depth of Light-box	Quantity P/Meter ²
80~120mm	96 pcs
130~160mm	50 pcs
170~250mm	30 pcs

Depth of Light-box	Qualitity 1 /Wictor
80~120mm	96 pcs
130~160mm	50 pcs
170~250mm	30 pcs

Colours available

R/G/B/Y/WW (special order times apply)

Match to Power Supply-12V:

≤ 56 pcs	18W
≤ 98 pcs	30W
≤ 193 pcs	60W
≤ 322 pcs	100W
≤ 483 pcs	150W
≤ 644 pcs	200W
	•

RoHS	VO Classified	
копо	UL Listed	
C€	Age Tested	
	Caution: ESD sensitive	

	Specification
LFD Type:	smd 3528 Everlight - specia

LED Type:	smd 3528 Everlight - specially designed for Outdoor use				
Colour:	White				
Luminous Flux (Im / LED)					
Red	Green	Blue	Yellow	White	Warm White
3	6	1.5	3	7~8 / 24	6~7
Wavelength Scope (nm) Color Temp (kelvin)			mp (kelvin)		
Red	Green	Blue	Yellow	White	Warm White

584~595

5500K ~ 6500K

2800K~3500K

463~475

Light Angle (2θ ½):	≥ 120°
	.=-
No' of LEDs per Module	3
Working Voltage:	12V DC
Power:	Max power use = .24 / module - 4.8 W / chain
Driving method:	Constant Voltage
Wires:	Grey: Positive; White: Negative
No' of modules / chain:	20
Max no' modules in series	25
Length of Chain:	2.5 Metres
Distance between modules:	7.5 cm
Shell Material:	ABS grease white
Module diamensions:	48mm(L)* 15mm(w)* 8mm(H)
Installation:	Screw / 3M double sided tape: 45mm(L)*12mm(W)*0.2mm
Working Temp:	-40°C ~+60°C
Storage Temp:	-50°C ~+80°C
IP Rating:	Waterproof - IP65
Warranty:	5 Years / 35,000 hours

Module diamensions: (unit: mm)



