

12V DC LED Flexible Strip Lighting



SASIGN INTERNATIONAL

web: signlighting.com.au




Noel Symon

Ph: 07 55649930

email: sales@sasign.com.au




suppliers of Acrylic Edge-Lighting systems & LED Lighting for Signage





IP22	
	Blue: 460-470nm 3528 Epistar 7.2W
	Red: 620-625nm 3528 Epistar 7.2W
	Green; 520-525nm 3528 Epistar 7.2W
	White- 6000k 3528 Epistar 7.2W

IP65	
	Blue: 460-470nm 2835 Epistar 12.0W
	Amber: 605-610nm 2835 Epistar 12.0W
	Red: 620-625nm 2835 Epistar 12.0W
	Green; 520-525nm 2835 Epistar 12.0W
	White- 6000k & 2700k 2835 Epistar 12.0W
	U/ Violet- 395-400nm 5050 Epistar- 14.4W
	White 6000K 3014 Epistar 9.4W

RGB	
	RGB- analogue 5050 Epistar- 14.4W
	RGB- digital SW 2811 5050 Epistar- 14.4W

IP67	
	White- 6000k & 2700k 2835 Epistar 12.0W
	RGB- analogue 5050 Epistar- 14.4W
	RGB- digital SW 2811 8mm heads 0.6W ea

Specifications:	
120 X 3528 Chips per meter	
Beam angle: 120 Degrees	
Can be Cut and Soldered every 3 chips (5CM)	
Working Temperature: - 30 to + 50 Celcius	
Diamensions 5M X 5mm X 3mm	
RoHS	V0 Classified
	UL Listed
ce	Age Tested
Caution: ESD sensitive	

Specifications:	
60 X Chips per meter	
Beam angle: 120 Degrees	
Can be Cut and Soldered every 3 chips (5CM)	
Working Temperature: - 30 to + 50 Celcius	
UV Stable: IP65- Silicon Glue	
Supplied with 3M Hight Performance adhesive	
Diamensions 2835 strip 5M X 9mm X 3mm	
5050 strip 5M X 10mm X 3mm	
5050 strip 5M X 10mm X 3mm	
3014 strip 5M x 10mm X 5mm	
120 chips perM	
RoHS	V0 Classified
	UL Listed
ce	Age Tested
Caution: ESD sensitive	

Specifications:	
strips - 60 X Chips per meter / string 10cm spacing	
Beam angle: 120 Degrees	
Can be Cut and Soldered every 3 chips (5CM)	
Working Temperature: - 30 to + 50 Celcius	
UV Stable: IP 67 silicon glue & Tube - Anti UV	
Supplied with 3M H/P adhesive	
Diamensions 2835 strip 5M X	
5050 strip 5M X 12mm X 5mm	
Digital string - 10cm max spa	
RoHS	V0 Classified
	UL Listed
ce	Age Tested
Caution: ESD sensitive	

The bitterness of poor quality remains long after the sweetness of low price is forgotten.