



SIGN LIGHTING AUSTRALIA
web: signlighting.com.au

Noel Symon
Ph 07 5564 9930
email: sales@signlighting.com.au



Suppliers of Acrylic Edge-Lighting systems and LED lighting for signage

Non Waterproof



Blue: 460-470nm
3528 Epistar 7.2W

Red: 620-625nm
3528 Epistar 7.2W

Green: 520-525nm
3528 Epistar 7.2W

White- 6000k
3528 Epistar 7.2W

Waterproof IP65



Blue: 460-470nm
2835 X 60 Epistar 12.0W

Amber: 605-610nm
2835 X 60 Epistar 12.0W

Red: 620-625nm
2835 X 60 Epistar 12.0W

Green: 520-525nm
2835 X 60 Epistar 12.0W

White- 6000k & 2700k
2835 X 60 Epistar 12.0W

U/ Violet- 395-400nm
5050 X 60 Epistar- 14.4W



RGB


White 6000K
3014 X 120 Epistar 9.4W

White 6500k
2835 X 60 Epistar 7.2W

Warm White 3000K
2835 X 60 Epistar 7.2W

RGB- analogue
5050 X 60 Epistar- 14.4W

RGB- digital SW 2811
5050 X 60 Epistar- 14.4W



Waterproof IP67



White- 6000k & 2700k
2835 Epistar 12.0W

RGB- analogue
5050 Epistar- 14.4W


RGB- digital SW 2811
8mm heads 0.6W ea



RGB

Specifications:

120 X 3528 Chips per meter
Beam angle: 120 Degrees
Can be Cut and Soldered every 3 chips (5CM)
Working Temperature: - 30 to + 50 Celcuis



Dimensions 5M X 5mm X 3mm

RoHS	VO Classified
	UL Listed
ce	Age Tested
Caution: ESD sensitive	

Specifications:


60 X Chips per meter
Beam angle: 120 Degrees
Can be Cut and Soldered every 3 chips (5CM)
Working Temperature: - 30 to + 50 Celcuis
UV Stable: IP65- Silicon Glue
Supplied with 3M Hight Performance adhesive

2835 strip 5M X 9mm X 3mm

5050 strip 5M X 10mm X 3mm

3014 strip 5M X 10mm X 5mm

2835 ZigZag 5M X 6.5mm X 2mm



RoHS	VO Classified
	UL Listed
ce	Age Tested
Caution: ESD sensitive	

Specifications:

strips - 60 X Chips per meter / string 10cm spacing
Beam angle: 120 Degrees
Can be Cut and Soldered every 3 chips (5CM)
Working Temperature: - 30 to + 50 Celcuis
UV Stable: IP 67 silicon glue & Tube - Anti UV
Supplied with 3M H/P adhesive

Dimensions 2835 strip 5M X

5050 strip 5M X 12mm X 5mm

Digital string - 10cm max spa

RoHS	VO Classified
	UL Listed
ce	Age Tested
Caution: ESD sensitive	

The bitterness of poor quality remains long after the sweetness of low price is forgotten.