





SIGN LIGHTING AUSTRALIA

web: signlighting.com.au

Noel Symon

Ph 07 5564 9930

email: sales@signlighting.com.au

s of Acrylic Edge-Lighting systems and LED lighting for signage

Specifications:



SAA / ERAC compliant and certified

5V 500 & 1500mA, 9V 1200mA, Available:

12V 500, 1500 & 2500 mAmps

Color - Black Diamensions -Vary

Reversable straight / 90 degree output C+ 2.1mm plug

Working Temperature: - 40 to + 40 Celcuis





Wall Adapters



Specifications:

12V DC - Constant Voltage

SAA / ERAC compliant and certified

Available in 5000 mAmp output

Supplied complete with input cable

Color - Black

Reversable straight / 90 degree output C+ 2.1mm plug

Working Temperature: - 40 to + 40 Celcuis







Specifications:

12V DC - Constant Voltage

SAA / ERAC compliant and certified

Available in 12.5 Amp output

Color - Chrome vented cover

Must be used in a safe environment

Working Temperature: - 40 to + 40 Celcuis



Waterproof



Specifications:

12V DC Output

SAA / ERAC compliant and certified

PFC>95%; precision +- 0.5V

Working temp: -50 to 70 Degrees C

Waterproof: IP 67

ALL with Aust plug

L150*W44*H32mm Diamensions: 30W (2.5A)

60W (5.0A) L180*W44*H32mm 100W (8.3A) L205*W68*H38 mm 150W (12.5A) L220*W68*H38 mm

200W (16.7A) L240*W70*H40 mm 360W (30A) L250*W80*H41 mm

The bitterness of poor quality remains long after the sweetness of low price is forgotten